


2X M2 X 0.4
THUMBSCREW

"P1"

MALE 68 PIN
PICO RIBBON
CONNECTOR
(0.8mm PITCH)

LENGTH

NICKEL PLATED
ZINC ALLOY HOODMOLDED HOOD
AND STRAIN RELIEF,
PVC, LIGHT GRAYUL STYLE 2990, 25 TWISTED PAIR, 28 AWG STRANDED
COPPER SPIRAL WRAPPED ALUMINIZED POLYESTER
SHIELD PLUS TINNED COPPER BRAID.
JACKET: PVC, COLOR: LIGHT GRAY (400C)

PIN 1

MALE 50 PIN
MICRO D-SUB
CONNECTOR
(.050" PITCH)

WIRING TABLE

HD68M	PAIR	HPDB50M	HD68M	PAIR	HPDB50M
6	1	1	19	13	14
40	1	26	53	13	39
7	2	2	20	14	15
41	2	27	54	14	40
8	3	3	21	15	16
42	3	28	55	15	41
9	4	4	22	16	17
43	4	29	56	16	42
10	5	5	23	17	18
44	5	30	57	17	43
11	6	6	24	18	19
45	6	31	58	18	44
12	7	7	25	19	20
46	7	32	59	19	45
13	8	8	26	20	21
47	8	33	60	20	46
14	9	9	27	21	22
48	9	34	61	21	47
15	10	10	28	22	23
49	10	35	62	22	48
16	11	11	29	23	24
50	11	36	63	23	49
18	12	13	30	24	25
52	12	38	64	24	50

DRAIN WIRE CONNECTED TO METAL FRAME OF EACH CONNECTOR

RoHS
compliant

MODEL NUMBER	LENGTH	
	METERS	FEET
M2MAD-6200-1.6	0.5	1.64
M2MAD-6200-3.0	1.0	3.28
M2MAD-6200-6.0	2.0	6.56
M2MAD-6200-10.0	3.0	9.84

NOTES:

CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.

APPROVAL:	
DESIGN BY:	RA
DESIGNED BY:	Phoenix
DRAWN BY:	Phoenix

M2MAD-6200-XXX

